










Product		Description / Standard Accessories	Model	Code
	Emax EVOlution Control Unit	Weight : 2.3 kg Power Source : AC 120/230V, 50-60Hz Dimensions : W130 x D254 x H97 mm	NE249 120	340438
	Standard Type Motor with Cord	Weight : 90 g (w/o Cord) with Straight Cord 1.5m Max. Torque 4.3 cN·m Max. Power : 73W Speed : 1,000~40,000 min-1 Accessory : Pin Spanner (K-233) 1 pc.	ENK-410S	339923
	Torque Type Motor with Cord	Weight : 147 g (w/o Cord) with Straight Cord 1.5m Max. Torque 4.8 cN·m Max. Power : 76W Speed : 1,000~25,000 min-1	ENK-250T	339924



 <p>Technical drawing of the Ring Type Attachment. It shows a cylindrical tool with a silver-colored front section and a black handle. Dimension lines indicate a total length of 64.2 mm and a diameter of 12.8 mm at the front end.</p>	<p>Ring Type Attachment</p>	<p>Weight : 92 g Collet Chuck : \varnothing3.0mm (CHH-3.0), \varnothing2.35mm (CHH-2.35) Accessory : Spanner (7 x 5.1) 1 pc. Pin Spanner (K-233) 1 pc. L Shaped Spanner 1 pc. 40,000 min-1 Max. (*) 40,000 min-1 Max. (*2)</p>	<p>IR-310</p>	<p>339937</p>
 <p>Technical drawing of the Lever Type Attachment. It features a black handle with a silver-colored front section and a lever mechanism. Dimension lines show a total length of 60 mm and a diameter of 13.2 mm at the front end.</p>	<p>Lever Type Attachment</p>	<p>Weight : 62 g Collet Chuck : \varnothing3.0mm (CHH-3.0), \varnothing2.35mm (CHH-2.35) Accessory : Spanner (7 x 5.1) 1 pc. Pin Spanner (K-233) 1 pc. 40,000 min-1 Max. (*) 40,000 min-1 Max. (*2)</p>	<p>IH-300</p>	<p>340271</p>
 <p>Technical drawing of the Straight Type Attachment. It has a black handle with a silver-colored front section. Dimension lines indicate a total length of 56.2 mm and a diameter of 18.1 mm at the front end.</p>	<p>Straight Type Attachment</p>	<p>Weight : 55 g Collet Chuck : \varnothing3.0mm (CHH-3.0), \varnothing2.35mm (CHH-2.35) Accessory : Spanner (7 x 5.1) 1 pc. Bar Wrench (PCR-30) 1pc. 40,000 min-1 Max. (*) 40,000 min-1 Max. (*2)</p>	<p>IG-400</p>	<p>340410</p>
 <p>Technical drawing of the 6 mm Torque Type Attachment. It features a grey handle with a silver-colored front section. Dimension lines show a total length of 102 mm and a diameter of 25 mm at the front end.</p>	<p>6 mm Torque Type Attachment</p>	<p>Weight : 210 g Collet Chuck : \varnothing6.0mm (CHG-6.0) Accessory : Spanner (10 x 10) 1 pc. Bar Wrench (K-212) 1 pc. Pin Spanner (K-233) 1 pc. * Use 6mm torque Type HG-200 to connect ENK-250T</p>	<p>HG-200</p>	<p>340242</p>

		30,000 min -1 Max. (*) 27,000 min-1 Max. (*2)		
	Long Type Attachment for Deep Hole Grinding ϕ 13 mm	Weight : 156 g Collet Chuck : ϕ 3.0mm (CHM-3.0) Accessory : Spanner (7 x 5.1), (6 x 4.5) 1 pc. each Pin Spanner (K-233) 1 pc. 35,000 min-1 Max. (*) 35,000 min-1 Max. (*2)	BMH-300	340245
	90° Mini Angle Type Attachment for Chamfering Deep Hole (Very Small Head)	Weight : 47 g Speed Reduction Ratio : 10/11 Collet Chuck : ϕ 1.6mm (K-253) Accessory : Chuck Wrench (K-232) 1 pc. Pin Spanner (K-233) 1 pc. 15,000 min-1 Max. (*1) 15,000 min-1 Max. (*2)	MFC-300M	340248
	90° Mini Angle Type Attachment for Chamfering Deep Hole	Weight : 50 g Speed Reduction Ratio : 10/11 Collet Chuck : ϕ 1.6mm (K-252) Accessory : Chuck Wrench (K-232) 1 pc. Pin Spanner (K-233) 1 pc. 15,000 min-1 Max. (*1) 15,000 min-1 Max. (*2)	MFC-300S	340247

	90° Angle Attachment	Weight : 45 g Collet Chuck : ø3.0mm (CHC-3.0) Standard Accessories (Rubber Pad, Paper Disk) Accessory : Standard Accessories 1 set. Chuck Wrench (K-231) 1 pc. Pin Spanner (K-233) 1 pc. 35,000 min-1 Max. (*1) 20,000 min-1 Max. (*2)	IC-300	340272
	50° Angle Attachment	Weight : 45 g Collet Chuck : ø3.0mm (CHC-3.0) Standard Accessories (Rubber Pad, Paper Disk) Accessory : Standard Accessories 1 set. Chuck Wrench (K-231) 1 pc. Pin Spanner (K-233) 1 pc. 35,000 min-1 Max. (*1) 20,000 min-1 Max. (*2)	KC-300	340273
	Mini-luster Attachment (Pencil-Type Polisher) (Reciprocating motion)	Weight : 130 g Max. tool shank diameter ø3.2mm, Screw clamp type. Stroke range (fixed) : 0.8mm Accessory : Standard Accessories 1 set 35,000 min-1 Max. (*1) 30,000 min-1 Max. (*2)	ML-8	340252

	<p>Swing-luster Attachment (Pencil-Type Polisher) (Right to Left motion)</p>	<p>Weight : 127 g Reciprocating Stroke (Variable) : 0~9,000 times/min. Stroke range (Variable) : 0~1.6mm Max. tool shank diameter ϕ5.0mm, Screw clamp type. Accessory : Standard Accessories 1 set 35,000 min-1 Max. (*1) 24,000 min-1 Max. (*2)</p>	<p>SLS-16</p>	<p>339878</p>
	<p>Fine Belt Sander Attachment</p>	<p>Weight : 350 g Belt Speed : 0~825 m/min. Belt Width : 4, 6, 8mm Accessory : 8, 6, 4mm Belts. Allen Wrench (3mm) : 1 pc. 35,000 min-1 Max. (*1) 35,000 min-1 Max. (*2)</p>	<p>KBS-101</p>	<p>340256</p>
	<p>Hammer Attachment for Engraving and Ornament Processing Work</p>	<p>Weight : 95 g Stroke Times : 25~5,000 times/min. Stroke Spring Pressure : 4.4~7.1N (Ring Adjustment Type) Accessory : Spanner (7 x 5.1) 1 pc. Bar Wrench (K-212) 1 pc. Oil and nozzle, Hammer Bit (For replacement) 2 pcs. 20,000 min-1 Max. (*1) 16,000 min-1 Max. (*2)</p>	<p>HA-500</p>	<p>340750</p>

	<p>Luster Attachment (Pistol-Type Polisher) (Reciprocating motion) Built-in Motor</p>	<p>Weight : 800 g Max. Torque 17.2 cN·m with Straight Cord 1.5m Stroke Range : 0~6mm (variable) Max. tool shank diameter ϕ6.4mm, Screw clamp type. Reciprocating Stroke (variable) : 0~7,600 times/min Accessory : Standard Accessories 1 set Lubrication Oil, Lubrication Nozzle for LUSTER 30,000 min-1 Max. (*1) 30,000 min-1 Max. (*2)</p>	<p>NLS-110</p>	<p>3400823</p>
	<p>Luster Attachment (Pistol-Type Polisher) (Reciprocating motion)</p>	<p>Weight : 680 g Stroke Range : 0~6mm (variable) Max. tool shank diameter ϕ6.4mm, Screw clamp type. Reciprocating Stroke (variable) : 0~7,600 times/min Accessory : Standard Accessories 1 set. Lubrication Oil, Lubrication Nozzle for LUSTER 30,000 min-1 Max. (*1) 30,000 min-1 Max. (*2)</p>	<p>LS-100</p>	<p>340251</p>
	<p>EXTENSION JOINT</p>	<p>Weight : 83 g Pin Spanner (K-233) : 1 pc. 35,000 min-1 Max. (*1) 35,000 min-1 Max. (*2)</p>	<p>CN-01</p>	<p>340260</p>

	(1/4) Speed Reducer	Weight : 68 g Pin Spanner (K-233) : 1 pc. 30,000 min-1 Max. (*1) 30,000 min-1 Max. (*2)	RG-01	340258
	(1/15) Speed Reducer	Weight : 93 g Pin Spanner (K-233) : 1 pc. 30,000 min -1 Max. (*1) 30,000 min -1 Max. (*2)	RG-02	340259